

2006年 06月 15日

環境關理 物質 不使用 證明書

會社名：히로세코리아(주)

部 署：품질보증팀

責任者：차 재환 차장



貴社에 販賣하는 製品 및 製品의 使用材料, 包裝材, 製造工程에
含有되는 添加劑 等に 對하여 貴社가 要求하는 管理水準
(使用禁止對象)의 物質을 使用하고 있지 않음을 證明합니다.
當社의 製品 및 製品의 使用材料, 包裝材, 製造工程에 含有되는
添加劑 等に 對하여 以下の 成分으로 構成되어 있음을 報告 합니다.

(1) 製品 使用素材

NO	제품명	부품명	원자재명	원자재 MAKER	비 고
1	DF30FC-24DP-0.4V(81)	HOUSING	LCP 6040GM	UENO	
		CONTACT	C5210R	NIKKO METAL	

(2) 測定可能物質의 ICP Data는 別紙 參照 要望

(3) 測定可能物質의 成分 分析 Data는 別紙 參照 要望

以上

Test Report No. JP/2006/03652 Date: March 28th, 2006

UENO FINE CHEMICALS IND, LTD.

2-4-8 KORAIHASHI, CHUO-KU, OSAKA-SHI, OSAKA

Report on the submitted samples said to be "UENO LCP 6040GM (Color: No.BK015RL, Lot No.: DL220-404091)"

Client Ref. No. : UENO05-003
Sample Receiving Date : 03/14/2006
Testing Period : 03/18/2006 TO 03/24/2006
Color, Appearance etc. of the sample : -LCP(Liquid Crystal Polymer) Pellet.

Test Result:

Test Item	Unit	Result	Method	Instrument	Detection Limit
Cd	ppm	N.D	EPA3052	ICP-AES	2
Pb	ppm	N.D	EPA3052	ICP-AES	2
Hg	ppm	N.D	EPA3052	ICP-AES	2
Cr6+	ppm	N.D	EPA3060A	UV-VIS	2

Note: N.D = not detected

* * * End of Report * * *

Signed for and on behalf of
SGS Far East Ltd.
Green Testing Center

Kuniyuki Goto
Laboratory Manager

Test Report No. JP/2006/03652 Date: March 28th, 2006

UENO FINE CHEMICALS IND, LTD.

2-4-8 KORAIBASHI, CHUO-KU, OSAKA-SHI, OSAKA

Report on the submitted samples said to be "UENO LCP 6040GM(Color:No.BK015RL, Lot No.:DL220-404091)"

Client Ref. No. : UENO05-004
Sample Receiving Date : 03/14/2006
Testing Period : 03/18/2006 TO 03/24/2006
Color, Appearance etc. of the sample : -LCP(Liquid Crystal Polymer)Pellet.

Test Result:

Test Item	Unit	Result	Method	Instrument	Detection Limit
PBBs			-	GC/MS	
Bromobiphenyl	ppm	N.D	—	GC/MS	5
Dbromobiphenyl	ppm	N.D	—	GC/MS	5
Tribromobiphenyl	ppm	N.D	—	GC/MS	5
Tetrabromobiphenyl	ppm	N.D	—	GC/MS	5
Pentabromobiphenyl	ppm	N.D	—	GC/MS	5
Hexabromobiphenyl	ppm	N.D	—	GC/MS	5
Heptabromobiphenyl	ppm	N.D	—	GC/MS	5
Octabromobiphenyl	ppm	N.D	—	GC/MS	5
Nonabromobiphenyl	ppm	N.D	—	GC/MS	5
Decabromobiphenyl	ppm	N.D	—	GC/MS	5

Note:N.D = not detected

No. JP/2006/03652 Date : March 28th, 2006

Test Item	Unit	Result	Method	Instrument	Detection Limit
PBDEs					
Monobromodiphenyl ether	ppm	N.D	—	GC/MS	5
Dibromodiphenyl ether	ppm	N.D	—	GC/MS	5
Tribromodiphenyl ether	ppm	N.D	—	GC/MS	5
Tetrabromodiphenyl ether	ppm	N.D	—	GC/MS	5
Pentabromodiphenyl ether	ppm	N.D	—	GC/MS	5
Hexabromodiphenyl ether	ppm	N.D	—	GC/MS	5
Heptabromodiphenyl ether	ppm	N.D	—	GC/MS	5
Octabromodiphenyl ether	ppm	N.D	—	GC/MS	5
Nonabromodiphenyl ether	ppm	N.D	—	GC/MS	5
Decabromodiphenyl ether	ppm	N.D	—	GC/MS	5

Note:N.D = not detected

* * * End of Report * * *

Signed for and on behalf of
SGS Far East Ltd.
Green Testing Center

Kuniyuki Goto
Laboratory Manager

Material Safety Data Sheet

Revised date Jan. 20, 2003

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name : UENO LCP 6040GM
Name of Company : UENO FINE CHEMICALS INDUSTRY,LTD.
Section in Charge : CHEMICALS DIV. QUALITY ASSURANCE DEPT.
Address : 2-4-8,KORAIBASHI,CHUO-KU OSAKA 541-8543
Phone No. : 81-6-6203-6193
Fax No. : 81-6-6222-2413
Emergency Phone No. : 81-795-68-7205

2. COMPOSITION INFORMATION ON INGREDIENTS

Chemical Family : Wholly Aromatic Liquid Crystal Polyester resin
Specification of Division : Composition
Ingredients and Composition : Resin 60wt%
Glass Fiber+Mineral 40wt%
Small amount of pigments may contain.
Serial No. in Official Gazette : (7)-2709 (base resin)
CAS-No. : 146647-94-1 (base resin)

3. HAZARDS IDENTIFICATION

Hazards : Not applicable
Harmfulness : Not applicable

4. FIRST-AID TREATMENT

Eye Contact : In the case of molten material , immediately flush and cool with clean water and seek medical attention.
In the case of solid or powder materials, immediately flush with clean water.
Seek medical attention if discomfort and incompatibility persist.

Skin Contact : In the case of molten material , immediately cool with clean water.
Do not forcedly peel off the solidified resin on the skin.
Seek medical attention if burned.

Inhalation : If nausea is caused by gas from the molten materials , remove immediately to fresh air.
When nausea persists, seek medical attention.

Ingestion : Help to vomit as much as possible . Seek medical attention if discomfort persists.

5. FIRE-FIGHTING MEASURES

Extinguishing Media : Water, Form fire-extinguishing agent, powder fire-extinguishing agent, Carbon dioxide gas

Extinguishing Measure : Recommend to use water for extinguishing.
Usual extinguishing measure is applicable.

Specific Harm : Incomplete combustion of the material may cause carbon mono-oxide , phenol and other toxic gases.

Protect of Extinguisher : Protective equipment such as gas mask should be worn.

6. ACCIDENTAL RELEASE MEASURES

Precautions of human : Clean up by broom or vacuum-cleaner to avoid slipping and tumbling by spilt pellets.

Precautions of environment: Follow the "Manual for preventing release of resin pellets" to avoid ingestion by marine organism and birds.

7. HANDLING AND STORAGE

HANDLING : Avoid to inhale emitted gas during molding.
Do not directly touch heated resin.

STORAGE : Do not store in high temperature and high humidity conditions, and avoid sunlight.
Stored away from fire and sources of heat.

8. EXPOSURE CONTROL /PERSONAL PROTECTION

Facility measures : In case of using molten material during molding, establish suitable local ventilation.
In case of using dust, use an airtight container with dust explosion proof.
Establish bodywash and eyewash equipments.

Protection

Eye protection : Wear safety glasses or goggles.

Body protection : In case of handling molten material during molding, wear heatproof gloves and long sleeve clothes in order to prevent thermal burns.

Respiratory protection : Wear dustproof mask.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Solid (pellet)

Melting Point : 320°C

Boiling Point : Not applicable

Vapor pressure : Not applicable

Specific Gravity : 1.74

Solubility in water : Insoluble

Flash Point : No data

Ignition Point : >540°C

Explosion Limit : Not applicable

Flammability : Flammable but self-extinguishing as keeping away from flame.

Ignitivity : Nonspontaneous ignition
Nonreactive with water

Oxidativity : None

Self-reactivity· explosively : None

Dust explosively : No data

10. STABILITY AND REACTIVITY

Stability· Reactivity : Stable and nonreactive on general handling and storage conditions.

11. TOXICOLOGICAL INFORMATION

Corrosive Property	: Unknown
Irritant Property	: Vapor generated during drying and molding may cause irritation to eyes and skins.
Acute Toxicity	: Unknown
Subacute Toxicity	: Unknown
Chronic Toxicity, Long-term toxicity	: Unknown
Carcinogenicity	: Unknown
Mutagenicity	: Unknown
Reproductive toxicity	: Unknown
Teratogenicity	: Unknown
Others	
Harmfulness of glass fibers	: Glass fibers of more than 5 μ m may cause itching . Skin irritation might form on occasion.

12. ECOLOGICAL INFORMATION

Biodegradability	: Unknown
Bioaccumulation	: Unknown
Fish Toxicity	: Unknown

13. DISPOSAL CONSIDERATIONS

This materials is classified as industrial waste and waste plastics based on "Law for treatment and cleaning of waste".

In case of disposal, ask approved industrial waste disposal agency or commission local governments in accordance with waste disposal law.

In case of burnout, use well-controlled incinerator and treat them in accordance with waste disposal law ,air pollution control law, and water pollution control law.

14. TRANSPORT INFORMATION

UN class and UN number: Not applicable

Notice : Avoid rough handling and contact with water in order to prevent break of bags.
Stack without drop and damage, and make sure to provide preventing load collapse.

15. REGULATORY INFORMATION

Disposal Regulation : Law for treatment and cleaning disposal waste.

16. OTHER INFORMATION

Ueno Fine Chemicals Industry, LTD. do not assume any liability whatsoever for the accuracy or completeness of the information contained herein, although stated information is prepared based on the

documents, information and data that can be obtained as far as possible.

This material safety data sheet is prepared for general use. Adequate safety and environmental countermeasures for actual uses and applications should be provided in case of unusual use.

株式会社エノモト 御中

2006年2月6日
日鉱金属加工株式会社 倉見工場
技術部 品質保証課

分析報告書

承認	作成
	

1. 分析結果

No.	試料名	成分	Pb	Cd	Cr	Hg	備考
		定量下限 単位	50ppm ppm	1ppm ppm	5ppm ppm	2ppm ppm	
1	C2680R(2006年2月3日測定)		<50	<1	<5	<2	PBB, PBDEにつきましては測定結果はありませんが弊社での使用はありません
2	C5191R(2006年2月3日測定)		<50	<1	<5	<2	PBB, PBDEにつきましては測定結果はありませんが弊社での使用はありません
3	C5210R(2006年2月3日測定)		<50	<1	<5	<2	PBB, PBDEにつきましては測定結果はありませんが弊社での使用はありません
4							
5							

2. 分析方法

- ① 測定試料数：試料数1で分析
- ② 前処理：硝酸での加熱分解
- ③ 六価クロム：総クロムとして分析
- ④ 分析装置：ICP発光分光分析装置(ICP-AES法)

To. HIROSE ELECTRIC CO., LTD.

MATERIAL SAFETY DATA SHEET

MSDS FILE No. (KURAMI WORKS) : 05-1114



(based on Form OSHA-174)

IDENTITY (AS Used on Label and List)

Product Class : Phosphor Bronze Strip
 Trade Name : JIS H3130 C5210R (Equivalent to ASTM B103 C52100)
 CAS No. : Copper: 7440-50-8, Tin: 7440-31-5, Phosphor: 7723-14-0
 Chemical Composition

	Content (wt-%)	CAS No.
Tin (Sn)	7.0~9.0	7440-31-5
Phosphor (P)	0.03~0.35	7723-14-0
Copper (Cu)	Balance	7440-50-8
Sn+P+Cu	99.7≤	-

Section I

Manufacturer's Name NIKKO METAL MANUFACTURING CO., LTD. KURAMI WORKS	Date Prepared January 27th, 2005
Address 3 Kurami Samukawa-cho Kouza-gun Kanagawa prefecture 253-0101 JAPAN	Signature of Person in Charge  MAKI, Tetsuo Senior Technical Supervisor, Quality Assurance
Telephone Number for Information (Quality Assurance) +81-467-75-7285	Signature of Person Responsible  WATANABE, Hiroaki Manager, Quality Assurance Section
Facsimile Number for Information (Quality Assurance) +81-467-74-6971	

Section II Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity : Names OSHA PeI ACGIH TLV)

Nothing for ordinary service condition

Section III Physical / Chemical Characteristics

Boiling Point	2630 °C for Copper 2275 °C for Tin	Specific Gravity (H2O = 1)	8.80
Vapor Pressure (mmHg)	N/A	Melting Point	1025 deg. centi. for C5210 Phosphor Bronze
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	N/A		
Appearance and Odor	Brown - Red (solid) : Odor - None		

Section IV Fire and Explosion Hazard Data

Flash Point (Method Used)	N/A	Flammable Limits	N/A	LEL	N/A	UEL	N/A
Extinguishing Media	N/A (stable , nonflammable substance)						
Special Fire Fighting Procedures	Not specified						
Unusual Fire and Explosion Hazards	Metal products do not present fire or explosion hazards under normal conditions.						

Section V Reactivity Data			
Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid)

Nothing

Hazardous Decomposition or Byproducts

Nothing

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI Health Hazard Data

Route(s) of Entry :	Inhalation ?	Skin ?	Ingestion ?
	N/A	N/A	N/A

Health Hazardous (Acute and Chronic)

N/A

Carcinogenicity :	NTP ?	IARC Monographs ?	OSHA Regulated ?
	N/A	N/A	N/A

Signs and Symptoms of Exposure

N/A

Medical Conditions

Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures

N/A

Section VII Precautions for State Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

N/A

Waste Disposal Method

Collect scrap for remelting.

Precautions to Be Taken in Handling and storing

For Handling

- Put safety gloves on to protect your hands from edges of coils which might cut your hands.
- Wear safety glasses when metal powders or chips are expected to be generated in the work.
- Put safety shoes on when handling heavy coils.

For Storing

- The environment of stocking area should be free from acid, alkali, chloride, sulfide and other corrosive chemicals to prevent from rusting or corrosion.

Other Precautions

No special requirements

Section VIII Control Measures

Respiratory Protection (Specify Type)

Wearing a mask be recommended in the work such as abrasion and buffing which generates metal powders or chips.

Ventilation	Local Exhaust	Special
	None	None
	Mechanical (General)	Other
	None	None

Protective Gloves

Put safety gloves on to protect your hands from edges of coils which might cut your hands.

Eye Protection

Wear safety glasses when metal powder is expected to be generated in the work.

Other Protective Clothing or Equipment

Put safety shoes on when handling heavy coils.

Work / Hygienic Practices

None

Influence to environments	Fish on toxicity : TLm 48 hr. on CuSO4
	Salmogaideneri : 0.038 ~ 0.8 ppm
	Oryzias Latipes : 2.1 ~ 24ppm